Using Artificial Intelligence for Object Localization in Autonomous Vehicles

Xiaobo Liu-Henke

Research Group for Control Engineering and Vehicle Mechatronics Ostfalia University of Applied Sciences Wolfenbüttel, Germany e-mail: x.liu-henke@ostfalia.de

Marian Göllner

Research Group for Control Engineering and Vehicle Mechatronics Ostfalia University of Applied Sciences Wolfenbüttel, Germany e-mail: mar.goellner@ostfalia.de

Abstract- The fast development of autonomous vehicles requires advanced technologies for precise object localization, which play a key role for the safety and efficiency of these systems. In this work, we present a novel Artificial Intelligence (AI) based algorithm for object detection and localization, specifically developed for use in autonomous vehicles. By integrating modern machine-learning methods and an innovative architecture, we were able to significantly increase the accuracy and processing speed of object localization. The algorithm was validated using a holistic model-based methodology with Model-inthe-Loop (MiL), Software-in-the-Loop (SiL), and Hardware-inthe-Loop (HiL) simulations, demonstrating its robustness and reliability. The results show that the approach pursued improves detection accuracy and minimizes response times, making it ideal for real-time application in interconnected cyberphysical traffic systems. This paper discusses both the theoretical foundations and the measurement results of the presented localization method, and underlines the potential of AI for the further development of autonomous mobility.

Keywords—autonomous vehicles; artificial intelligence; object localization; machine learning; validation of AI algorithms; real-time systems.

I. INTRODUCTION

The revolution in the field of mobility, particularly through the introduction of Autonomous Vehicles (AVs), is on the cusp of significant technological breakthroughs. At the heart of this transformation are modern control engineering techniques extended with Artificial Intelligence (AI), which plays a key role in the development and optimization of autonomous vehicle systems. A critical aspect for the functionality and safety of these vehicles is the ability to precisely localize surrounding objects, such as other road users, pedestrians, or traffic signs. AI based technologies are becoming increasingly important in the area of object localization.

This article focuses on the methodological development of an innovative object detection and localization algorithm based on AI and designed specifically for use in autonomous vehicles. A central challenge here is the complex machine Sven Jacobitz Research Group for Control Engineering and Vehicle Mechatronics Ostfalia University of Applied Sciences Wolfenbüttel, Germany e-mail: sve.jacobitz@ostfalia.de

Taihao Li

Research Group for Control Engineering and Vehicle Mechatronics Ostfalia University of Applied Sciences Wolfenbüttel, Germany e-mail: ta.li@ostfalia.de

learning for each new object type to be localized. However, this effort can be significantly reduced by using a new type of architecture. The developed AI approach is able to process and interpret complex environmental information in order to ensure precise object localization. This combines extensive knowledge from various successful research projects, such as the Lower Saxony Future Mobility Lab.

The aim of this paper is to discuss the theoretical and practical aspects of AI-assisted object localization and to contribute to the further development of intelligent autonomous vehicles. By combining theoretical research and practical experiments, the aim is to gain a deeper understanding of the potential of AI in the domain of autonomous vehicles and to provide a solid starting point for future innovations.

The structure of this article is as follows: Section II is devoted to the discussion of the current state of knowledge, including aspects of object detection and localization. Section III deals with the model-based development methodology for interconnected cyber-physical systems. In Section IV, the concept of an innovative intelligent function for object localization is developed. This begins with the definition of requirements and evaluation metrics, followed by a discussion of the architecture and the concepts of self-localization and object detection. Finally, the machine learning method used is explained. Section V briefly summarizes the results of the various investigations to assess the new object localization. The article ends in Section VI with a summary and an outlook.

II. STATE OF KNOWLEDGE

The following section discusses the state of knowledge on localization and object detection methods.

A. Localization methods

Localization plays a central role in the navigation of AVs. Numerous methods have already been proposed and implemented. Effective navigation and safe driving are based on precise self-localization, which requires a real-time sampling rate at the millisecond level and accuracy down to the

Courtesy of IARIA Board and IARIA Press. Original source: ThinkMind Digital Library https://www.thinkmind.org

centimeter [1]. This self-localization forms the basis for accurate position estimation of other detected objects.

Recently, sensor technologies for vehicle localization have developed significantly [2]. A sensor data fusion of Global Navigation Satellite Systems (GNSS), Light Detection and Ranging (LiDAR) systems and cameras contributes to highly effective localization. In addition, the movement of the vehicle can be tracked and estimated through the use of Inertial Measurement Units (IMU) and odometry. This approach to active localization offers both flexibility and increased precision.

Furthermore, localization techniques can be roughly divided into map-based and non-map-based methods. Mapbased positioning, which uses common map-matching algorithms, integrates LiDAR [3], camera [4] and wireless communication [5]. It proves to be more accurate and more suitable for determining the position of a vehicle in a global coordinate system. In contrast, non-map-based localization, usually realized by Simultaneous Localization and Mapping (SLAM), provides accurate mapping of the environment independent of existing maps, especially for indoor applications. A detailed investigation of existing map-based localization algorithms and their most important mechanisms is given in [6].

B. Object detection approaches

Numerous approaches have been developed in object detection research, which can be roughly divided into traditional methods and modern techniques based on machine learning [7].

Early techniques, such as edge detection and segmentation use simple features to detect object boundaries and similar visual features in images. These approaches are fast and less computationally intensive, but often offer lower accuracy and robustness in complex or variably lit scenarios [8].

The introduction of deep learning, in particular Convolutional Neural Networks (CNNs), has revolutionized object detection. Architectures, such as R-CNN, YOLO and SSD achieve a high level of accuracy by learning from large amounts of data automatically [9]. These functions are able to recognize objects nearly in real time, making them ideal for applications in AV. Current research focuses on improving accuracy under different conditions and reducing false alarms to further optimize the technologies [10].

In summary, it can be said that, despite the numerous research efforts, there is currently no seamless object detection and localization approach with sufficient accuracy and realtime capability for use in autonomous vehicles.

III. METHODOLOGY

A structured, systematic approach is required to develop AI-based functions for complex cyber-physical systems. The complexity of autonomous vehicles in particular poses a special challenge due to the high degree of internal and external networking and the growing number of intelligent and powerful hardware and software components. For this reason, the holistic, verification-oriented, model-based design methodology based on Rapid Control Prototyping (RCP) with Modelin-the-Loop (MiL), Software-in-the-Loop (SiL) and Hardware-in-the-Loop (HiL) simulations has been established [11].

The core of the methodology is the iterative mechatronic development cycle according to [11] as shown in Figure 1. Starting with the requirements and specifications, the system is first modeled and analyzed. The function is initially designed and optimized offline using a data management system. Once a sufficient level of functionality has been achieved, the function is transformed into C code via automatic code generation and tested and further optimized using SiL. The function is then automatically implemented on real-time hardware and further optimized and tested under real-time conditions using HiL simulations.



Figure 1. Mechatronic development cycle according to [11].

By using this structured, seamless model-based development process, AI-based functions can be developed in a focused and efficient manner.

IV. CONCEPT OF THE INTELLIGENT OBJECT LOCALIZATION

As shown in section II, there is currently no seamless realtime-capable function for object localization. The following section therefore deals with the detailed conception of the AIbased object localization algorithm for AV. Based on the requirements specified, evaluation metrics are established for the machine learning methods that will be used later. The central aspect is the architecture of the new function. Finally, the approaches of the specific localization algorithms and the machine learning used are discussed.

A. Requirements and evaluation metrics

In the development of an AI function for object localization for AV, specific requirements manifest themselves that affect both the precision and reliability of localization as well as the integration capability and scalability of the AI systems. Firstly, the AI function must be highly accurate in order to reliably determine the position and movement of surrounding objects even under varying and potentially challenging environmental conditions. Secondly, the dynamic nature of the traffic environment requires a high reaction speed and realtime capability to support time-critical decisions. Third, the AI localization function must demonstrate robust performance against sensor data inconsistencies and failures, which implies advanced error handling and tolerance. Finally, the architecture of the AI function must be modular and flexible to allow easy integration into different vehicle platforms and to adapt to future technological developments. Compliance with these requirements is crucial to ensure the safety and effectiveness of autonomous vehicles in complex and unpredictable environments and to ensure their acceptance and trustworthiness by end users.

Given these diverse and demanding requirements, it is clear that a precise and comprehensive evaluation of AI functions is essential. This need leads to the development and application of specific metrics that are able to measure and validate the effectiveness and reliability of AI-driven localization systems in detail. Key metrics include localization accuracy, which is usually measured as the mean square error between the estimated and actual positions of objects. In addition, robustness to sensory interference and environmental variability is critical, assessing the consistency of localization results under different operating conditions.

The response time of the AI function, defined as the time between data acquisition and the provision of localization information, is also critical, especially in dynamic traffic environments where quick decisions are required. Finally, the ability to integrate into existing vehicle systems plays a role in the evaluation, taking into account compatibility and the impact of the AI function on system resources. The careful selection and application of these evaluation metrics enables a sound assessment of AI object localization capabilities and supports the continuous optimization of these essential systems in autonomous vehicles.

In particular, the metrics Average Precision (AP) and mean Average Precision (mAP) are used to evaluate the performance of the developed algorithms for object detection and localization. The AP measures the quality of an AI model in terms of its ability to correctly detect and localize objects within a predefined class (e.g., cars, trucks, etc.). It is determined by integrating the precision-recall curve p(r) according to equation (1). This curve represents the relationship between the accuracy of recognition (precision) and the proportion of correctly identified positive cases (recall). A higher AP value indicates better performance in relation to the class under consideration.

The mAP value, calculated according to equation (2), aggregates the AP values across N predefined detection classes and thus provides a comprehensive measure of the overall performance of the detection and localization system. The mAP value is particularly meaningful for applications where multiple object classes need to be detected simultaneously. This metric shows the average performance of the system across all classes, which enables a holistic evaluation of the algorithms.

$$AP = \int_{0}^{1} p(r) dr \tag{1}$$

$$mAP = \frac{1}{N} \sum_{i=1}^{N} AP_i$$
⁽²⁾

B. Architecture of the novel AI function

The architecture of the new AI function is characterized by its modularity and flexibility, which enable efficient integration and processing of various sensor data. It implements a multi-layered modularized approach with data collection and sensor data fusion, self-localization of the vehicle, object detection and external localization (see Figure 2).



Figure 2. Architecture of the new AI based localization function.

This ensures high cohesion within the modules and low coupling between them. Core of the architecture is the use of advanced machine learning and AI algorithms, which enable precise and robust localization information to be extracted from the raw, multimodal sensor data. This architecture underlines the potential of a systematic and modular approach to the development of complex solutions for autonomous vehicles and provides a solid basis for further research and development in this dynamic field.

C. Sensor data fusion for self-localization

Figure 3 shows the concept of self-localization according to [12]. The interface to the inputs and outputs of the function is defined. The LiDAR and IMU mounted on the vehicle can

Courtesy of IARIA Board and IARIA Press. Original source: ThinkMind Digital Library https://www.thinkmind.org

be used for self-localization. The LiDAR scans the environment and transfers the data to the localization function block in the form of a point map.



Figure 3. Concept of the self-localization function according to [12].

The IMU can be used to detect the movement of the AV in order to implement the local localization function. The localization function module also receives information from the map, camera and LiDAR. By comparing the map information with the measurement information from the built-in sensors, the AV can then be localized (global localization). Finally, the function module also receives image information from an external reference camera, a sensor in the traffic environment. The camera is permanently installed in the application scene and records the position of the vehicle for validation and correction. For this purpose, each vehicle in the laboratory setup is clearly identified by two infrared LEDs. The position transmitted by the camera is regarded as the reference position of the vehicle. In addition to validation, this reference position can be transmitted to the AV in order to eliminate self-localization errors.

D. Object detection and localization

The innovative AI-based object detection and localization is based on the use of neural networks. The core of the approach lies in the integration of CNNs, which have been specially trained to recognize relevant objects from a variety of sensor inputs, such as camera images and radar or LiDAR data. These networks are able to extract and learn complex features from the input data, enabling precise object detection even under difficult environmental conditions, such as poor lighting conditions or rapid changes in the field of view.

The object detection concept also relies on a robust parallel data processing architecture as shown in Figure 4, which enables efficient handling and analysis of large volumes of data. This is based on smart tagging using an existing, pretrained neural network (e.g., YOLO) and a specialized detection network. The results of both networks are merged and provide robust object detection. A box surrounding the object marks the detected areas.



Localization is based on the transformation of the received fused detected data into a bird's eye view. Using geometric transformation, the object coordinates can be determined relative to the vehicle's own position.

E. Machine Learning Method

The neural network used is specially developed and trained for detection and positioning in 3D environments. The training process of this network includes the generation of a suitable training data set that maps the object features to be detected with sufficient accuracy. It is particularly important to ensure that the training data covers the entire possible event space of the use case in order to guarantee a high degree of generalizability and reliability in real application scenarios. The data sets are either recorded under realistic conditions or generated by an image-realistic simulation and include a wide range of scenarios and object positions in order to effectively prepare the network for detection and precise localization.

During training, various criteria based on the metrics presented in Section IV.A are used in a loss function to optimize the accuracy of object localization, using machine-learning methods. Figure 5 illustrates an example of the progression of a loss function during the learning process. The calculated loss value is plotted against the number of training steps performed. A downward trend can be seen. However, due to the special learning procedure for finding a global minimum, fluctuations are included. The training process is terminated when a termination criterion is met, such as falling below a limit value or reaching a maximum number of steps.

Finally, the trained network is validated through tests under real conditions in order to confirm the performance and reliability of the localization algorithm.

V. RESULTS OF THE OBJECT LOCALIZATION

For initial tests, the designed function for object detection and localization was trained to recognize a special laboratory vehicle using about 2000 data records. These data sets are generated automatically with the help of CAD software. Subsequently, the function was tested in detail using MiL simulations. These were used for the initial validation of the algorithms. Particular attention was paid to the accuracy of object positioning to ensure that the algorithm accurately detects the environment and reliably localizes objects.



Figure 5. Sample loss history during training.

In the subsequent SiL and HiL phases, the interaction between real test vehicles and the algorithms was examined under realistic conditions. The SiL tests focused on refining the algorithms by simulating different traffic scenarios and object interactions, enabling a comprehensive evaluation of the algorithm performance under different conditions. The HiL tests extended these investigations by incorporating real hardware to test the algorithms under real-time conditions. These tests showed that the developed algorithms are robust to different environmental conditions and capable of precise localization in dynamic scenarios.

For basic optimization, validation and performance analysis, the test setup shown schematically in Figure 6, is first used in the laboratory. A laser-based reference sensor is utilized to verify the results of the algorithm. A camera captures a defined image section. Vehicles are positioned at different angles and orientations to the camera in a referenced grid.



Vehicles at different angles and orientations

Figure 6. Schematic test setup for the first verification of AI-based object localization

Figure 7 illustrates an example of the result of a localization in a laboratory environment. The detection and localization of an autonomous vehicle can be seen, outlined in red. The analysis of the test results revealed a high efficiency and accuracy of the developed object detection and localization algorithms. By applying specific metrics, such as mAP and evaluating the required computing power, the performance of the algorithms could be quantitatively assessed. The results confirm that the algorithms not only have a high detection rate, but also perform localization with good accuracy.



Figure 7. Exemplary localization result in a laboratory environment.

The computation time required by the function is a critical factor in the performance of the developed object detection function, especially in applications that require fast response times, such as autonomous vehicles. The efficiency of the algorithm has therefore been intensively optimized to minimize the latency between data acquisition and decision making. By using optimized neural network architectures and advanced hardware acceleration techniques, the processing time has been significantly reduced. This makes it possible to process even complex scenes with multiple objects to be localized. The versatile tests under various operating conditions have shown that object detection and localization is performed within less than ten milliseconds. A Raspberry Pi 4 single-board computer with hardware acceleration was used for this purpose.

VI. CONCLUSION AND FUTURE WORK

This publication presents a novel AI-based algorithm for object localization in autonomous vehicles. By developing a new architecture and using modern machine learning techniques, the authors were able to significantly increase the accuracy and efficiency of object recognition. Various optimizations and tests, including MiL, SiL and HiL simulations, confirmed the effectiveness of the approach, making the algorithm a solid basis for practical application in the navigation of autonomous vehicles.

The research results provide a promising basis for future developments in AI-assisted object localization. It is expected that further optimizations, especially in terms of reducing false alarms and increasing algorithm efficiency, will improve the applicability in real traffic situations. In addition, the integration of further sensor technologies and an increased focus on interdisciplinary research could further increase the

Courtesy of IARIA Board and IARIA Press. Original source: ThinkMind Digital Library https://www.thinkmind.org

accuracy and robustness of localization systems in order to make autonomous vehicles safer and more reliable.

ACKNOWLEDGMENT

Funded by the Lower Saxony Ministry of Science and Culture under grant number ZN4172 in the Lower Saxony Advance of the Volkswagen Foundation and supervised by the Center for Digital Innovations (ZDIN).



REFERENCES

- Y. Lu, H. Ma, E. Smart, and H. Yu, "Real-Time Performance-Focused Localization Techniques for Autonomous Vehicle: A Review," *IEEE Trans. Intell. Transport. Syst.*, vol. 23, no. 7, pp. 6082–6100, 2022, doi: 10.1109/tits.2021.3077800.
- [2] S. Campbell, N. O'Mahony, et al., "Where am I? Localization techniques for Mobile Robots A Review," in 2020 6th International Conference on Mechatronics and Robotics Engineering (ICMRE), Barcelona, Spain, 2020, pp. 43–47. doi: 10.1109/ICMRE49073.2020.9065135.
- [3] X. Zhang, Z. Li, and Y. Wang, "Global Localization based on Road-centric 3D Point Cloud Descriptor in Urban Environments," in 2022 6th CAA International Conference on Vehicular Control and Intelligence (CVCI), Nanjing, China, 2022, pp. 1–6. doi: 10.1109/CVCI56766.2022.9965007.
- [4] H.-Y. Lin and C.-H. He, "Mobile Robot Self-Localization Using Omnidirectional Vision with Feature Matching from Real and Virtual Spaces," *Applied Sciences*, vol. 11, no. 8: 3360, 2021, doi: 10.3390/app11083360.
- [5] Y. Yan, I. Bajaj, R. Rabiee, and W. P. Tay, "A Tightly Coupled Integration Approach for Cooperative Positioning Enhancement in DSRC Vehicular Networks," *IEEE Trans.*

Intell. Transport. Syst., vol. 23, no. 12, pp. 23278–23294, 2022, doi: 10.1109/TITS.2022.3208257.

- [6] L. Li, M. Yang, B. Wang, and C. Wang, "An overview on sensor map based localization for automated driving," in 2017 Joint Urban Remote Sensing Event (JURSE), Dubai, United Arab Emirates, 2017, pp. 1–4. doi: 10.1109/JURSE.2017.7924575.
- [7] S. Kaur, A. L. Yadav, and A. Joshi, "Real Time Object Detection," in 2022 International Conference on Cyber Resilience (ICCR), Dubai, United Arab Emirates, 2022, pp. 1–5. doi: 10.1109/ICCR56254.2022.9995738.
- [8] J. Parekh, P. Turakhia, H. Bhinderwala, and S. N. Dhage, "A Survey of Image Enhancement and Object Detection Methods," in *Advances in Intelligent Systems and Computing, Advances in Computer, Communication and Computational Sciences*, S. K. Bhatia, S. Tiwari, S. Ruidan, M. C. Trivedi, and K. K. Mishra, Eds., Singapore: Springer Singapore, 2021, pp. 1035–1047. doi: 10.1007/978-981-15-4409-5_91.
- [9] J. S. Murthy, et al., "ObjectDetect: A Real-Time Object Detection Framework for Advanced Driver Assistant Systems Using YOLOv5," *Wireless Communications and Mobile Computing*, vol. 2022, pp. 1–10, 2022, doi: 10.1155/2022/9444360.
- [10] C. Gupta, N. S. Gill, P. Gulia, and J. M. Chatterjee, "A novel finetuned YOLOv6 transfer learning model for real-time object detection," *J Real-Time Image Proc*, vol. 20, no. 3, pp. 1–19, 2023, doi: 10.1007/s11554-023-01299-3.
- [11] X. Liu-Henke, et al., "A Holistic Methodology for Modelbased Design of Mechatronic Systems in Digitized and Connected System Environments," in *Proceedings of the 16th International Conference on Software Technologies*, Online conference 2021, pp. 215–223. doi: 10.5220/0010566702150223.
- [12] X. Liu-Henke, T. Li, M. Göllner, S. Jacobitz: "Self-Localization with internal an external sensors in the Labortery test field". In *Proceedings of the 3rd International Conference on Computers and Automation (CompAuto 2023)*, Paris, France, 07.12. 09.12.2023, pp. 1–6.